

Specifications

Engine Performance
Engine Power
Max Torque
Rated engine speed
Engine
Engine type / no. of Cylinders / Capacity / Aspiration
Transmission type
12 x 12 Side shift
Power take-off
Single speed PTO - 540 rpm
Steering
Hydrostatic
Hydraulics
3-point linkage control
Lift capacity
Hydraulic pump capacity
System Pressure
Spool valves
1 x DA / FL
Brakes
Туре
Standard wheels and tyres
Front 2WD / 4WD
Rear
Weights and Dimensions
Weight without ballast - Semi-platform 4WD
Length
Height with ROPS / Canopy
Wheelbase
Capacities
Fuel tank

	MF 5709	MF 5710
ISO hp (kW)	92 (69)	102 (76)
Nm @1500 rpm	380	410
	2200	2200
	AGCO Power AP44 / 4 / 4400cc / Turbocharged	
	•	•
	•	•
	•	•
	Lever operated ELC	Lever operated ELC
Max Kg	4500	4500
Litre/min	57	57
bar	200	200
	•	•
	Oil immersed	Oil immersed
	10.00x16 / 380/85 R24	10.00x16 / 3380/85 R24
	460/85 R34	460/85 R34
Kg	3600	3600
mm	4755	4755
mm	2711	2711
mm	2431	2431
Litres	170	170

Standard



MF 5700

- 2 NEW models, 92 hp to 102 hp from the AGCO power four cylinder engines
- All new 12x12 synchronised transmission in two ranges.
- 2WD and 4 WD axles

Key features

- ROPS and Canopy
- 57 I/min hydraulic pump flow
- 1 spool valve standard
- 540 independent PTO.
- Flat floor platform Operator Station



For even greater productivity a range of optional equipment is available. For full details please consult your local Massey Ferguson dealer.

Every effort has been made to ensure that the information contained in this publication is as accurate and current as possible. However, inaccuracies, errors or omissions may occur and details of the specifications may be changed at any time without notice. Therefore, all specifications should be confirmed with your Massey Ferguson Dealer or Distributor prior to any purchase.

